

Foundry	Process	Type	Special	Voltage	Data						
					Count of LVS	Count of DRC	Count of PEX	Count of Calibrati	Count of DFM	Count of LFD	
Chartered	0.045	-	-	-						1	
	0.065	-	-	-						1	
		Logic	-	-	-	1	1		1		
	0.13	ANA	ANA/Mixed Signal/RF	ip	1.2V/3.3V/5.5V		1				
			ANA, LOGIC, SF, SRAM	Logic/Mixed Signal/RF	1.2V/3.3V/5.5V		1				
		ANA/LOGIC/LPLOGIC/RF	ip	1.2V/3.3V/5.5V					1		
		ANA/LOGIC/RF	0.4UM Top Metal	1.2V/3.3V/5.5V		1					
			Nominal	1.2V/3.3V/5.5V		1					
		ANA/RF	Dual Passivation	1.2V/3.3V/5.5V						1	
			Single Passivation	1.2V/3.3V/5.5V						1	
		Logic	LDMOS	5V				1			
	ip		1.2V/3.3V/5.5V		1						
	0.18	LOGIC/MIXED/SRAM	Salicide	1.2V/2.5V/3.3V/5V	1	1		1			
	0.25	LOGIC/MIXED/SRAM	Salicide	1.8V/2.5V/3.3V	1	1		1			
	0.35	Logic/MIXED	Salicide/Polycide	2.5V/3.3V	1	1		1			